

www.spectrapipes.com



Crafted for a heated flow

CPVC PLUMBING SYSTEMS

CPVC PLUMBING SYSTEMS

Spectra CPVC plumbing systems are manufactured with the best raw materials and strict quality control in production, which gives these products very high consistency, making them ideal for both hot and cold water distribution.



FEATURES & BENEFITS



Withstands Temperature of up to 93° Celcius



Low Thermal Conductivity



Strong & Durable



UV Resistant

Product Range

Pipes	3/4" to 2"
Fittings	3/4" to 2"


Standards

Pipes	IS 15778
Fittings	ASTM D 2846

Applications

- Indoor and outdoor use for hot and cold water applications (up to 93°C)
- RO and DM water plants
- For concealed, down take & terrace looping
- Residential and commercial buildings
- Public utilities, swimming pools & industrial applications

Dimension of CPVC Pipes



Nominal Size		Outer Diameter (D) in mm		SDR 11 - Class 1				SDR 13.5 - Class 2			
				Wall Thickness (t) in mm		Working Pressure at		Wall Thickness (t) in mm		Working Pressure at	
MM	Inch	Min	Max	Min	Max	27°C	82°C	Min	Max	27°C	82°C
20	3/4"	22.1	22.3	2.00	2.50	27.60	6.80	1.70	2.20	21.80	5.50
25	1"	28.5	28.7	2.60	3.10	27.60	6.80	2.10	2.60	21.80	5.50
32	1 1/4"	34.8	35.0	3.20	3.70	27.60	6.80	2.60	3.10	21.80	5.50
40	1 1/2"	41.2	41.4	3.80	4.30	27.60	6.80	3.10	3.60	21.80	5.50
50	2"	53.9	54.1	4.90	5.50	27.60	6.80	4.00	4.60	21.80	5.50

HEAD OFFICE

No.21, Kumara Krupa Road, Opp. Hotel Solitaire, Bengaluru - 560 001 | Ph: 080 - 4266 0000 | E: contact@spectrapipes.com